



TPG 261, controller for 1 transmitter

For operation of one ActiveLine transmitter



Pfeiffer Vacuum · Headquarters/Germany

Tel. +49 (0) 6441 802-0 · Fax +49 (0) 6441 802-202 · info@pfeiffer-vacuum.de · www.pfeiffer-vacuum.net

TPG 261, controller for 1 transmitter


TPG 261



- ▶ For operation of one ActiveLine transmitter
- ▶ Simple to operate
- ▶ Easy readable display

[Similar Image](#)

Dimensions



| | |
|---|----------|
| A | 128.5 mm |
| B | 70.8 mm |
| C | 228.5 mm |
| D | 82 mm |
| E | 2.5 mm |

TPG 261, controller for 1 transmitter

| Technical Data | TPG 261, controller for 1 transmitter |
|-----------------------------------------------|-------------------------------------------------------|
| Connections for transmitter | 1 |
| Display rate | 10 1/s |
| Error signal: Working contact, potential-free | 1 piece |
| Error signal: Switching voltage max. | 60 V DC |
| Filter time constant | 1.2 / 0.4 / 0.02 s |
| Interface | RS-232-C |
| Mains requirement: frequency (range) | 50/60 Hz |
| Mains requirement: power consumption | 45 VA |
| Mains requirement: voltage (range) | 90-250 V |
| Measurement range max. | 55000 mbar |
| Measurement range min. | 5·10 ⁻¹¹ mbar |
| Measurement rate | 50 1/s |
| Protection category | IP 30 |
| Safety | EN61010-1 / EN 50081-1 / EN50082-2 / IEC1010 |
| Set point: Changeover contact, potential-free | 2 pieces |
| Set point: Current max. | 1 A |
| Set point: Voltage max. | 60 V DC |
| Signal output: Measuring value, analog | 0-10 V |
| Temperature: Operating | 5-50 °C |
| Temperature: Storage | -20 - +65 °C |
| Weight | 1.1 kg |

| | |
|---------------------|-----------------|
| Order number | PTG28030 |
|---------------------|-----------------|

| Accessories | TPG 261, controller for 1 transmitter |
|--------------------|---------------------------------------------|
| Sensor cable, 10 m | PT448252-T |
| Sensor cable, 15 m | PT448253-T |
| Sensor cable, 20 m | PT448254-T |
| Sensor cable, 25 m | PT448255-T |
| Sensor cable, 30 m | PT448256-T |
| Sensor cable, 35 m | PT448257-T |
| Sensor cable, 3 m | PT448250-T |
| Sensor cable, 40 m | PT448258-T |
| Sensor cable, 45 m | PT448259-T |
| Sensor cable, 50 m | PT448260-T |
| Sensor cable, 6 m | PT448251-T |